

ANTI SLIP STEP COVERS - ABP



Highly versatile, heavy duty pre-formed step covers and nosing. Robust GRP provides a corrosion resistant surface for damaged, worn or slippery steps. Anti-Slip Step Covers will tolerate heavy wear and has excellent slip resistance even in wet conditions.



Availability

Anti Slip Step Covers are available in a range of sizes 600mm, 750mm, 800mm, 1000mm, 1200mm, 1500mm, 2000mm and 3000mm in length by up to 345mm.

Available as black with a 55mm nosing in white or yellow, or available in stone colour.

Surface Preparation

Patch repair badly damaged or dished steps using a suitable filler or strong cement mix. Epoxy Repair Mortar is ideal if heavy use is anticipated.

Application

Dry fit the tread to ensure that it is the correct size and lays flat on the surface. If required it can be trimmed to size using an industrial jigsaw and appropriate cutting blades (Bosch TIOI AIF or similar are ideal). The tread is pre-drilled for mechanical fixing to damp, dirty or friable surfaces.

We recommend the following fixings:

To timber: 30mm x 5mm zinc plated or stainless steel screws.

To steel plate: No.8 x 20mm self-tapping pan head Pozi stainless steel screws or No.8 x 20mm self-drilling pan head Philips zinc plated screws.

To concrete: 30mm x 5mm zinc plated or stainless steel impact anchors (Hilti HPS-1 or similar).

To open mesh: stainless steel or zinc plated saddle clips and dome head bolts suitable in length for the depth of the existing treads.

Alternatively, the tread can be glued to sound, clean, dry surfaces using a suitable high strength gap filling adhesive (Gripfill or similar).

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings for
Industry*