

**Tarmacoat is a tough, flexible acrylic paint for tarmac or asphalt**

**Appearance**

Tarmacoat is available in white, tile red, light blue, light grey and mid green. It dries to a low to mid sheen finish depending on the substrate.

**Availability**

The product is supplied in 5 litre units.

**Limitations**

Tarmacoat will not bind or fill weak, decayed surfaces. Do not apply in constantly wet areas.

**Storage**

Store in a cool, dry place out of direct sunlight.

**Shelf Life**

At least one year in manufacturer's unopened containers.

**Surface Preparation**

Surfaces must be clean, sound and either dry or slightly damp. Solvent Free Degreaser may be used to remove oil and grease from the surface. Existing flaking paint or exceptionally smooth surfaces should be mechanically abraded to remove loose material and also improve adhesion.

**Application**

A single, even coat should be applied by either brush or medium pile roller. Avoid applying too thickly. On rough, uneven or porous surfaces, a second coat may be applied after one hour. Work should not begin if rain or temperatures under 10°C are expected.

**Coverage**

5 litres covers 20 - 30m<sup>2</sup> (single coat) depending on the texture of the surface. The coverage rate does not allow for filling the crevices and texture of a tarmac or asphalt surface. Using the product in this way will greatly reduce coverage and extend drying time.

**Curing**

Cold or wet conditions will delay curing. Under normal conditions, the area may be used for light traffic after 24 hours, with 48 hours curing time required for normal use.



**SPECIALIST PAINTS FOR INDUSTRY**

### **Safety Precautions**

No food products should be allowed near the area during application and drying. All product labels provide general safety information. Material Safety Data Sheets are available.

### **Solvent Free Degreaser**

A solvent-free product recommended for preparatory degreasing. 5 litres covers 20m<sup>2</sup> maximum.

All products are sold subject to the Company's Standard Conditions of Sale.

The Company and its representatives are often asked to comment on potential uses of products that differ from those described in the Company's data sheets. Whilst in such cases the Company and its representatives will always try to offer helpful and constructive advice, the Company cannot be held responsible for the results of such uses unless they are specifically confirmed in writing by the Company.

All information is based on results gained from experience and testing and is believed to be accurate, but it is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control.

**Paco systems**  
Broadridge Close  
Newton Abbot  
Devon TQ12 1YE

Tel: 01626 207064  
[www.paco-systems.co.uk](http://www.paco-systems.co.uk)  
[info@paco-systems.co.uk](mailto:info@paco-systems.co.uk)

*Paints and Coatings for  
Industry*