

Anti Fly-Poster Coating

Description:

A non hazardous, water based coating based on tough Polyurethane resins and a novel texturing agent. The combination provides a high degree of anti-stick properties in a simple to apply coating which has excellent adhesion to metal, wood, brick, plasticised vinyl and other plastics.

Properties:

Specific Gravity	1.01 gm/ml
Appearance	Thick gel
Colour	Clear
Number of coats	Two
Cleaner	Water
Flash Point	Non Flammable
Drying Times	
Touch	35 - 45 minutes [20°C., 60% RH]
Hard	12 hours
Overcoating	1.5 to 2 hours [20°C., 60% RH]
Coverage Rate	Circa 3 to 5 square metres per Litre [Very dependant upon surface type and its porosity]

Application Methods

IMPORTANT! Stir well before use to incorporate the texturing grit.

Brush or roller. Apply generously onto the area to be treated with a brush. Even out the surface by gently brushing at right angles to the original application.

Do not over brush.

Best applied with either a short haired roller or open textured foam roller.

Surfaces must be sound, grease free and clean of all debris and contamination.

Apply when the relative humidity is below 80% RH.

For external application, only apply at temperatures above 5°C when rain is unlikely during application or drying.

Cleaning

Clean spillages and equipment with clean water and/or warm soapy water.

Storage

Store in covered, ventilated areas out of direct sunlight between 5 & 25°C. Keep away from frost.

Safety Data

Not classified as hazardous however we recommend the use of plastic gloves and safety glasses when using the product.

Note: The information given above is, to the best of our knowledge, true and accurate. However it is given as guidance only and is not to be taken as a warranty of the results.

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings for
Industry*