

EXTERIOR STUBBORN GRAFFITI REMOVER

LONDON UNDERGROUND PART NOS: 17418/134 & 17418/135

CONCENTRATED BRUSH-ON GEL PAINT, VARNISH AND GRAFFITI REMOVER AVAILABLE WITH ADDED PUMICE.

- ü *Non-flammable*
- ü *Non caustic/non acidic formulation*
- ü *Viscous for use on vertical surfaces*
 - ü *All purpose*
 - ü *Water washable*
 - ü *Will penetrate several layers*
- ü *Graffiti Types: permanent felt tip inks, leather dyes, aerosol spray paint, Lipstick and wax crayon. From: unpainted metal, wood, concrete and brick (smooth and rough).*

APPLICATION

EXTERIOR STUBBORN GRAFFITI REMOVER (ESGR) is an all purpose jelly paint stripper that easily removes decorative coatings/finishes such as paints, cellulose, enamel, polyurethane and modern acrylic from all metals and wood. Excellent non-drip characteristics to enable use on vertical surfaces. For industrial and domestic use.

EXTERIOR STUBBORN GRAFFITI REMOVER is primarily used in removing painted graffiti from masonry and unpainted metal and wood. Suitable on permanent felt tip ink, leather dyes, aerosol spray paint, lipstick and wax crayon.

METHOD OF USE

Shake the container before use. Apply a generous coating of *EXTERIOR STUBBORN GRAFFITI REMOVER* using a stiff brush or cotton swab. Remove softened paint with a wooden scraper and rinse off residue with water. Exceptionally heavy layers of paint may require a second application. For graffiti work in well, leave it in contact with the surface for 30 mins (longer if required). Wipe off product and graffiti working outside to in, using a cotton swab. Wash off residual graffiti and ESGR using a pressure hose if appropriate (use hot/cold water at 150-200 psi). For persistent graffiti stains, repeat the above steps until no further removal is possible. Coverage normally 2-4 sq metres per litre.

SAFETY PRECAUTIONS

Use outdoors where possible or in a well ventilated area. Wear chemically resistant goggles or a visor. Wear rubber (not pvc) gloves and overall/apron. Wash off any splashes with plenty of soap and water. Eyes should be treated by irrigation with water. Do not allow the paint remover to enter water courses or the foul sewer. For detailed health and safety information request a hazard data sheet.

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*