

HIGH FLASHPOINT LUBRICANT AND DEMOISTURISING SPRAY

- § SYNTHETIC HYDROCARBON OIL BASED
- § BASE FLASHPOINT 77°C (OVER 50% ABOVE NORMAL LUBRICANT DEMOISTURISING SPRAYS)
- § CO₂ PROPELLED
- § LOW ODOUR/COLOURLESS
- § PTFE MICROSUSPENSION FOR ADDED LUBRICITY AND TO MINIMIZE FRICTION
- § NON CONDUCTIVE AND WATER RESISTANT
- § PROVIDES LONG LASTING PROTECTION

HF Lube 77 is a multi purpose lubricant spray utilizing a synthetic base fluid, with additives to inhibit corrosion.

The product incorporates a micronised suspension of PTFE to enhance lubricity and therefore minimize friction.

It provides a high strength, wide temperature lubricant film with water displacement and protection properties.

HF Lube 77 helps: -

- § Prevent electrical failures
- § Improves electrical performance
- § Does not dry out or become brittle or hard
- § Protects against salt, air condensation, water, corrosive fumes and gases

APPLICATIONS

HF Lube 77 will displace water and moisture, lubricate and protect from wear and corrosion. It will ease rusted and seized components and stop squeaking caused by surface friction. This multi use product can be used on: -

Coils, distributors, generators, spark plugs, starter motors, electrical circuitry, mechanical tools and equipment, motors, power tools, batteries, controls & switches, VDU's, office equipment etc.

Available in cartons of 12x400ml cans

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*