

PC99 ANTI-VANDAL COATING

PRODUCT DESCRIPTION

A non-oxidising, non-setting coating formulated using a selection of various petroleum derivatives and durable pigments. This product is recommended by various police forces as an anti-intruder coating and to act as a deterrent to burglars and vandals against entry into dangerous areas.

PC99 has the benefits of a wide working temperature from -20°C up to 60°C.

Can be applied to most surfaces, low odour and solvent free.

USES

For use on drain pipes, sills, tops of wall and fences, garage and porch roofs, flat roofs etc, trees (to discourage theft of eggs), electricity pylons to prevent access to dangerous areas, telegraph poles, lamp posts to prevent climbing.

TECHNICAL PROPERTIES

Colour	Black, Grey, Red		
Finish	Slight Sheen		
Curing Agent	N/A		
Mix Ratio	N/A		
Specific Gravity	0.99		
Volume Solids	100%		
Recommended Film Thickness	400-500µ WFT / 400-500µ DFT		
Theoretical Spreading Rate	2-2.5 m ² /litre		
Application Method	Brush		
Flash Point	150°C		
VOC	0 g/litre		
Drying Times	10°C	20°C	30°C
Touch Dry	This product does not dry		
Hard Dry	This product does not dry		
Minimum Overcoat	This product does not dry		
Maximum Overcoat	This product does not dry		

RECOMMENDED SYSTEMS

One coat system.

SURFACE PREPARATION

Remove all oil, grease etc. by detergent washing and rinsing with clean fresh water. Wire brush to remove loose dirt, existing paint flakes and any rust or corrosion products. Ensure that the surface to be coated is dry.

PRODUCT APPLICATION

Mixing Mix well before use.
Thinners Do not thin. If the product appears too thick to apply, warm product up to reduce viscosity.
Brush Apply to recommended film thickness.
Cleaner White Spirit.

Cleanup Considerations

All equipment should be cleaned immediately after use with White Spirit. Ensure all waste materials (including packaging) are disposed of in accordance with local regulations.

HEALTH, SAFETY & ENVIRONMENTAL

This product must be used in accordance with the Material Safety Data Sheet supplied by the manufacturer.

The user must observe local health, safety and environmental regulations when using this product.

Consult the manufacturer if there are any concerns over the suitability of this product.

PACK SIZES 5 litre, 2.5 litre.

PACK WEIGHTS 5 litre : 4.95 kg. 2.5 litre : 2.475 kg.

STORAGE CONDITIONS

Store in a cool, dry shaded area. Shelf life 12 months.

LIMITATIONS

Do not apply this product if the relative humidity exceeds 90% or if the substrate is within 3°C of the dew point.

Do not use on surfaces likely to be used by bona fide persons. We recommend applying the product at least 2.3 m. (7 feet) above ground level.

Do not apply other surface coatings over PC99.

To remove this coating use scrapers and wash surface with White Spirit.

It would be prudent to erect a 'Warning Notice'.

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*



SPECIALIST PAINTS FOR INDUSTRY

DISCLAIMER

The information given in these specifications and technical advice - whether verbal, in writing or by way of trials is for guidance and is given in good faith, but without warranty. This also applies where propriety rights or third parties are involved. Any person using these products without first making further enquiries as to the suitability of the products for the intended purpose and testing the products to assess their fitness for the purpose does so at their own risk. The application, use and processing of the products are beyond our control and are therefore your own responsibility, and we can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. The information contained in these data sheets is liable to modification from time to time in the light of experience and our policy of continuous development.

It is the user's responsibility to ensure that this sheet is current prior to using the product.

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*