

SOLVENT PAINT STRIPPER

**A SPECIALLY FORMULATED CONCENTRATE FOR COLD OPERATIONS,
CONTAINING ACTIVATORS AND INHIBITORS FOR PAINT STRIPPING.**

- CONTAINS MILD ACID ACTIVATOR
- SAFE ON STEEL, ALUMINIUM AND COPPER
- REMOVES MOST TYPES OF PAINT
- LOW TOXICITY
- COLD OPERATION-NO HEATING COST
- WATER RINSEABLE

PCS 205A has had widespread use in removing mastic, glue and rubber residues from heat exchangers.

METHOD OF USE

1 part **PCS 205A** is mixed with 3 parts by volume of PDS 100. This is mixed in a steel tank and 2-3 inches of cold water is added to prevent evaporation. The articles to be stripped are then immersed in the tank and left for up to 12 hours depending on the type of coating. Remove articles from the tank and rinse with cold water.

SAFETY PRECAUTIONS

Although non-flammable always use in a well ventilated area. No smoking in this area. Avoid contact with skin and clothing. Wear protective clothes, eye shield and apron. Splashes on skin should be washed off with plenty of soap and water. Splashes in the eye should be treated by irrigation and medical advice sought immediately. **PCS 205A** should not be used with Magnesium and can cause slight attack on zinc alloys, but this is normally acceptable. For detailed health and safety information request a hazard data sheet.

PACKAGING

25 and 205 litre drums.

Paco systems

Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel/Fax: 01626 207064
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*