

PDS100 SOLVENT

**A solvent paint stripper/degreaser specially formulated for cold operations.
Contains dichloromethane and stabilizers.**

APPLICATIONS

PDS100 is used as a degreaser/paint remover in immersion tanks, for most types of metal (Avoid contact with aluminium). PDS100 can be used to strip paint from wood and inks from printing machines. The product is also widely used in the plastics field to fuse acrylic plastics e.g. PDS100 is also used to replenish old paint strippers to prolong life of the solution.

METHOD OF USE

Use a dip tank constructed of mild steel. Add a 3 inch water seal to the surface to act as a vapour seal to prevent evaporation. Immerse components totally and below the water seal to prevent discolouration from the water phase. When the grease/paint is lifted allow the components to drain and pressure rinse with water.

To extend the life of the product , a fine mesh sludge tray is recommended so that paint residues can be removed from the tank regularly. Do not heat or agitate.

SAFETY PRECAUTIONS

Harmful by inhalation.

Use in a well ventilated area.

Wear protective clothing to prevent contact with skin and eyes.

Wash off any splashes with plenty of soap and water.

Eyes should be treated by irrigation with water.

For detailed health and safety information request a hazard data sheet.

PACKAGING 4 x 5, 25 and 200 litre drums. Bulk supplies also available on request.

N.B. If you require a similar product for use in a vapour degreaser please ask for details on PDS100 SVG.

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*