

## PERF 95

NON-FLAMMABLE, ECONOMICAL, ALL PURPOSE SOLVENT CLEANER  
DEGREASER.

Perf 95 is the new performance solvent; generating a wealth of ideas, especially where low cost, low toxicity, excellent solvency and high boiling point are factors. Perf 95 is a mixture of refined dimethyl esters and is characterised by its mild odour and low vapour pressure.

The Dimethyl Esters are manufactured from a mixed acid stream to the specifications below.

### SPECIFICATIONS

INGREDIENTS	WEIGHTS %	CAS NO.	EEC NO.
DIMETHYL SUCCINATE	15 - 26	106-65-0	203-419-9
DIMETHYL GLUTARATE	55 - 67	1119-40-0	214-277-2
DIMETHYL ADIPATE	12 - 23	627-93-0	211-020-6
COLOUR HAZEN MAX. 16			
WATER CONTENT MAX WEIGHT % 0.2			
DIESTER CONTENT WEIGHT % MIN 99			
ACIDITY mg KOH/g MAX. 0.5			
APPEARANCE CLEAR COLOURLESS LIQUID.			

### SOLVENTS WHICH CAN BE REPLACED.

Perf 95 or blends of Perf 95 with other low cost solvents can successfully replace the following solvents:-

ISOPHORONE	GLYCOL	ETHER ACETATES
METHYLENE CHLORIDE	BUTYL DIGLYCOL	GLYCOL ETHERS
HIGH BOILING KETONES	ETHYL ETHOXY PROPIONATE	
CRESYLIC ACID	CYCLOHEXANONE	

**Paco systems**  
Broadridge Close  
Newton Abbot  
Devon TQ12 1YE

Tel: 01626 207064  
Fax: 08712 424345  
[www.paco-systems.co.uk](http://www.paco-systems.co.uk)  
[info@paco-systems.co.uk](mailto:info@paco-systems.co.uk)

*Paints and Coatings  
for Industry*

**APPLICATIONS:-** PERF 95 offers an extremely safe, low toxicological but powerful alternative to traditional solvents in a wide range of industrial applications.

COIL COATINGS. CLEANING CHEMICALS. POLYESTER & EPOXY PRIMERS, PAINT STRIPPERS, FOUNDRY CORE BINDERS, HIGH GLOSS STOVING ENAMELS, AUTOMOBILE TOP COATS, GRAFFITI REMOVERS, HAND CLEANERS, TEXTILE LUBRICANTS, G.R.P RESIN CLEANING, MAGNETIC WIRE ENAMELS. WOOD FINISHES. ACRYLIC LAQUERS PESTICIDES & INSECTICIDES. PLASTIC SUBSTRATE FINISHES, PRINTING INKS, HIGH QUALITY THINNERS, SEALANTS & WAX, FORMULATIONS, PLUS MANY OTHERS.

**SAFETY PRECAUTIONS:-** Classed as non-hazardous. May cause irritation. Avoid contact with skin and eyes. Eye contact should be flushed away by irrigation. Skin contact should be washed off with water.

Use in a well ventilated area away from sources of heat or ignition. For detailed health and safety information, request a hazard data sheet.

**PACKAGING:** 25 and 205 litre drums

**Paco systems**  
Broadridge Close  
Newton Abbot  
Devon TQ12 1YE

Tel: 01626 207064  
Fax: 08712 424345  
[www.paco-systems.co.uk](http://www.paco-systems.co.uk)  
[info@paco-systems.co.uk](mailto:info@paco-systems.co.uk)

*Paints and Coatings  
for Industry*