

## **PERTUFF**

### **INTRODUCTION**

Performance Pertuff is specifically designed to improve cleaning efficiency while overcoming the limitations imposed by liquid caustic based cleaning compounds. Performance Pertuff can also be used as a deodorizing wash in all applications. Performance Pertuff is extremely effective on the cleaning and removal of heavy contamination of inert gas soot.

### **APPLICATION**

Our general recommendations are for cleaning tanks for inert gas residues to a degree of cleanliness where no contaminants are to be tolerated in the next cargo. Recirculate or inject Performance Pertuff at 3% to 5% strength in fresh water, for light contamination, after the tanks have been stripped and rinsed. Modified procedures and percent solutions vary with other cargoes. Performance Pertuff can also be applied neat in spray applications followed by a rinse.

### **GENERAL DOSAGE OF THE PRODUCT**

Rust and stain removal 2-5%  
Oil removal 4-8%  
Interior cleaning 1-5%  
Immersion baths 10-100%  
Fish oils 3-5%  
Hydrocarbons 3-5%

**PACKAGING:** 25 litre drums

**Paco systems**  
Broadridge Close  
Newton Abbot  
Devon TQ12 1YE

Tel: 01626 207064  
Fax: 08712 424345  
[www.paco-systems.co.uk](http://www.paco-systems.co.uk)  
[info@paco-systems.co.uk](mailto:info@paco-systems.co.uk)

*Paints and Coatings  
for Industry*