

GENERAL PURPOSE DEGREASER & TANK CLEANER

<p>PRODUCT DESCRIPTION A heavy-duty solvent emulsifier economical and ready to use, containing petroleum solvents, emulsifiers and surfactants, used as a tank cleaner or for general degreasing.</p> <p>DIRECTIONS FOR USE AND DOSE RATES * PES 30 is recommended for local cleaning and degreasing and conventional means. Apply undiluted over soiled area and allow a contact time of between 15-30 minutes before rinsing off with water. * SOAK METHOD: Put parts to be cleaned into a bath of PES 30 undiluted for heavy soil, for medium to light soiling use a solution of between 10-30% PES 30 in water. Parts should be soaked for at least 30 minutes before washing off with water. * SPRAY METHOD: Spray PES 30 undiluted over all soiled areas. Allow time for PES 30 to act, between 15-30 minutes, then rinse off by water hose. For stubborn deposits, agitation by scrubbing will assist the cleaning operation. IN SERVICE CLEANING: This method may be undertaken with engine running at normal speed.</p>	<p>FEATURES AND BENEFITS</p> <ul style="list-style-type: none"> § Wide application range - from tank cleaning to heavy duty degreasing. § Wide cleaning spectrum - effective on mineral oils and petroleum based chemicals. § Powerful solvent with quick penetration and emulsifying properties. § Rapid rinsing, leaving clean oil-free surfaces. § Safe to use on most metal surfaces, painted surfaces and tank linings. § Recommended for use with high pressure and steam cleaning equipment. <p>APPLICATIONS</p> <ul style="list-style-type: none"> § Cargo tank cleaning of mineral oils and petroleum based chemicals. § Cleaning oil coolers, fuel oil preheaters, lube oil heat exchangers. § Cleaning and degreasing of cooling water systems prior to descaling operations. § Degreasing double bottom, deep tanks and bilges etc. § Removal of general oil contamination from machinery and engine room. § Cleaning/degreasing of boilers. § Soak cleaning of machinery parts.
---	---

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*