

Plastisol Re-coat.

TECHNICAL DATA

STANDARD COLOURS	Plastisol Range, BS4800 & RAL
DRY FILM APPEARANCE	Satin Smooth
SPREADING RATE	12 to 15 m ² p/lit.
TOUCH DRY @ 20°C	1 hours.
RECOATING TIME @ 20°C	4 Hours
AVERAGE WET FILM THICKNESS	90 Microns
AVERAGE DRY FILM THICKNESS	45 Microns .
SOLIDS by VOLUME.	53%
VOLATILE ORGANIC COMPOUNDS.	480 Gms/Lt.
APPLICATION METHODS .	Brush, Roller or Spray
SUBSTRATES	Suitably cleaned and dry surfaces
THINNERS & TOOL CLEANING.	Thinners type KPT04 (White Spirit)
FLASH POINT.	Above 32°C
PACK SIZES.	5lt, 20lt, 25lt & 205lt
SHELF LIFE.	12 Months.
MIN' APPLICATION TEMPERATURE	7°C

PRODUCT FEATURES,

- * Tough Surface Finish
- * Re-coats Plastisol
- * Flexible system
- * Good Adhesion
- * Light Fast Pigments
- * Single Pack Material

DESCRIPTION & RECOMMENDED USES

This product is formulated as an easy to use system where the re-coating of Plastisol type sheetings are required. This is a versatile material widely used on all types of box formed and corrugated sheeting. (NOTE: Corrugated sheeting has a surface area that is approximately 50% greater than the floor space it covers.)

APPLICATION

Stir well prior to use. The paint is best applied by Brush or Roller although after thinning it can be applied by Spray. Surfaces should be free from surface contamination such as grease, oil, loose or flaking materials.

HEALTH and SAFETY See separate Health and Safety sheet.

The Manufacturer follows a process of continuous improvement that may lead to specification changes, also the actual application method and substrate are beyond our control. This Data Sheet is issued for general guidance only. It is based on tests and information believed to be correct at the time of printing. All recommendations issued by or on behalf of the company are subject to the companies conditions of sale.

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings for
Industry*