

PR402E THICK

GELLED SCALE & CEMENT/MORTAR STAIN REMOVER

Application

PR 402E THICK is a concentrated, inhibited, hydrochloric acid based cleaner. It can be used to remove mortar and cement stains from brickwork, paving and tiles encountered in all types of industrial and domestic situations. **PR 402E THICK** acts by removing the top surface layer to reveal lower layers which appear as good as new. **PR 402E THICK** will also remove soot stains, rust stains and calcium deposits in toilets. This gelled version is ideal for use on vertical surfaces, to increase dwell time when removing scale etc.

Method of use

Use neat for brickwork. If in doubt test a small area. Apply by brush and agitate if necessary. Rinse off thoroughly with clean water. Neutralize with alkali before disposal to drain. Avoid prolonged contact.

Safety Precautions

Take normal precautions for handling concentrated acids. Do not mix with bleach or any products containing hypochlorite. Do not heat or use on hot surfaces and make sure that there is adequate ventilation. Avoid contact with skin and eyes. Splashes to skin should be washed off with water. Eye contact should be rinsed away by irrigation with clean water. For detailed health and safety information request a hazard data sheet.

Packaging: 25 litre containers.

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*