

Anti-slip Decking Paint

Technical Data:

Dry film appearance	Clear, finely textured with a special Tear Drop shaped additive that remains suspended in the paint thus eliminating, "Bald patches" a common fault with cheaper aggregate systems.
Spreading rate	8 to 12 sq/mts p/ltr subject to porosity / deck profile.
Touch Dry @ 20°C	2 hours
Hard dry @ 20°C	Overnight
Average wet film thickness	100 microns
Average dry film thickness	52 microns
Solids by volume	52% (+/- 2%)
V.O.C. content	570 grams p/ltr
Application methods	Roller or brush
Substrates	Clean dry decking surfaces
Thinners & tool cleaning	White spirit.
Flash point	Above 32°C
Pack sizes.	750mls, 2.5lts.
Shelf life.	12 months
Min. application temperature	7°C

Product benefits:

- * Tough anti-slip finish.
- * Clear finish.
- * Easy to apply.
- * Provides safety underfoot.
- * Prevents slips & trips.
- * Excellent weathering properties.

Description and recommended uses:

Specifically formulated for exterior use on decks, steps & slopes etc.
Dries to a Clear finely textured finish that is tough, durable, with excellent anti-slip properties.
Recommended for use on decks, steps, ramps and inclines.
Ideal for exterior & interior use on wooden decks, concrete or metal steps and slopes etc.

How to apply:

1. Sweep up loose debris.
2. Ensure the deck is clean and dry.
3. Apply with a good quality brush or roller.
4. Touch dry in 2 hours.
5. Through dry overnight.
6. Clean tools with White Spirit.

Health & Safety: See separate Health and Safety Data sheet.

The manufacturer follows a process of continuous improvement, which may lead to specification changes; also the actual application method and substrate are beyond our control. This Data Sheet is issued for general guidance only. It is based on tests and information believed to be correct at the time of printing. All recommendations issued by or on behalf of the company are subject to the companies' conditions of sale.

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings for
Industry*