

## **PR 402E** **CEMENT AND MORTAR STAIN REMOVER** **TOILET AND WASHROOM DESCALER**

### **Application**

**PR 402E** is a concentrated, inhibited, hydrochloric acid based cleaner. It can be used to remove mortar and cement stains from brickwork, paving and tiles encountered in all types of industrial and domestic situations. **PR 402E** acts by removing the top surface layer to reveal lower layers which appear as good as new. **PR 402E** will also remove soot stains, rust stains and calcium deposits in toilets.

### **Method of use**

For brickwork dilute 1:1 with water. For terrazzo, marble, coloured paving, tiles, sand lime/silicate bricks etc use a 1:4 solution of **PR 402E** with water. If in doubt test a small area. Apply by brush and agitate if necessary. Rinse off thoroughly with clean water. Neutralize with alkali before disposal to drain. Avoid prolonged contact. For heavy duty toilet and washroom descaling use neat or diluted with up to 20 parts water depending on the degree of soiling. Allow sufficient dwell time, agitate if necessary.

### **Safety Precautions**

Take normal precautions for handling concentrated acids. Do not mix with bleach or any products containing hypochlorite. Do not heat or use on hot surfaces and make sure that there is adequate ventilation. Avoid contact with skin and eyes. Splashes to skin should be washed off with water. Eye contact should be rinsed away by irrigation with clean water. For detailed health and safety information request a hazard data sheet.

### **Packaging**

4 x 5 litre & 25 litre containers

**Paco systems**  
Broadridge Close  
Newton Abbot  
Devon TQ12 1YE

Tel: 01626 207064  
Fax: 08712 424345  
[www.paco-systems.co.uk](http://www.paco-systems.co.uk)  
[info@paco-systems.co.uk](mailto:info@paco-systems.co.uk)

*Paints and Coatings  
for Industry*