

SUPERWASH

SUPERWASH is a non-caustic, non-hazardous, liquid blend of surfactants, alkali and solvent in concentrated form. The product is a powerful, biodegradable degreaser removing soil from hard surfaces. Suitable for both domestic and industrial use.

APPLICATIONS

SUPERWASH can be used in a variety of applications to remove grease, grime and traffic film from walls, floors, paintwork, plastic, machinery, equipment, engines, lorry and tanker bodies, railway/underground rolling stock etc. Superwash is suitable for use in pressure washers, steam cleaners and foaming equipment in applications where some foam or a stable foam is desirable.

USAGE INSTRUCTIONS

For walls floors and paintwork use Superwash at a dilution of between 1 and 2% in water. Apply by spray, brush or sponge.

For machinery and vehicle bodies use Superwash at a dilution between 1 and 2% in water. Apply by spray, brush or sponge.

For pressure washing and steam cleaning use in the detergent tank at a dilution of between 1 and 2% in water.

In all applications higher concentrations may be required depending on the degree of soiling. After use rinse off with clean water.

PACKAGING:

25 litre drums

NB At dilutions of 11% or less the pH of a solution of Superwash will be below 11.

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*