

GRAFFITI GHOSTING REMOVER

- ü HIGHLY ACTIVE
- ü WATER WASHABLE
- ü CONTAINS NO CHLORINATED SOLVENTS
- ü BIODEGRADABLE

APPLICATIONS

GRAFFITI GHOSTING REMOVER is for use on all types of stone and masonry where traditional graffiti removers have left shadows.

METHOD OF USE

Use neat for ghosting removal . Apply a generous coat of **GRAFFITI GHOSTING REMOVER** using a soft alkali resistant brush or spray. Allow a contact time of up to 5 minutes then remove, preferably with a pressure washer and hot water. Repeat if necessary.

GIVE AREA A FINAL WASH WITH ACID NEUTRALIZER IF REQUIRED Surrounding areas should be protected. Do not allow product to dry out completely. **Always test on surface to be treated before use**

SAFETY PRECAUTIONS:

Use in a well ventilated area. Avoid contact with skin or eyes. Wear chemical resistant goggles or visor. Wear rubber (not pvc) gloves and overalls. Splashes to skin should be washed off with plenty of water. in the event of eye contact, irrigate with clean water. For detailed health and safety information request a hazard data sheet.

PACKAGING: 4 x 5 litre drums

Paco systems
Broadridge Close
Newton Abbot
Devon TQ12 1YE

Tel: 01626 207064
Fax: 08712 424345
www.paco-systems.co.uk
info@paco-systems.co.uk

*Paints and Coatings
for Industry*

ACID NEUTRALIZER FOR GHOSTING REMOVER

- ü HIGHLY ACTIVE
- ü ACTS AS BRICK AND STONE CLEANER
- ü WATER WASHABLE
- ü CONTAINS NO CHLORINATED SOLVENTS
- ü BIODEGRADABLE

APPLICATIONS

ACID NEUTRALIZER FOR GHOSTING REMOVER is for use on stone and masonry after **GRAFFITI GHOSTING REMOVER** has been applied to the surface. It may also be diluted up to 4 times with water for use as a general brick/concrete cleaner.

DO NOT USE on limestone or polished surfaces and always test on an inconspicuous area before use.

METHOD OF USE

Use neat as afterwash. Spray or brush onto the damp surface and allow to dwell for 2-3 minutes. Thoroughly rinse off with water.

Dilute 1 - 4 times with water to use as general brick/concrete cleaner. Surrounding areas should be protected.

Always test on surface to be treated before use

SAFETY PRECAUTIONS:

Use in a well ventilated area. Avoid contact with skin or eyes. Wear chemical resistant goggles or visor. Wear rubber (not pvc) gloves and overalls. Splashes to skin should be washed off with plenty of water. In the event of eye contact, irrigate with clean water. For detailed health and safety information request a hazard data sheet.

PACKAGING: 4 x 5 litre drums

Paco systems

Broadridge Close

Newton Abbot

Devon TQ12 1YE

Tel: 01626 207064

Fax: 08712 424345

www.paco-systems.co.uk

info@paco-systems.co.uk

*Paints and Coatings
for Industry*